5000i HD

Large, heavy duty fume extraction unit






Description & features

- Clear & informative graphic display
- Highest grade HEPA and carbon technology
- Automatic electronic flow control maintains a constant extraction rate even as the filter blocks
- Gas and particle sensors to warn the operator
- Larger filter capacity for high dust applications

Filters



Specifications

	3 phase supply	
Voltage	220v	400v
Part Number	0LX5575D	0LX5570D
Wattage	7.5kW	
Frequency	50Hz / 60Hz	
Cabinet Height	1804mm	
Cabinet Width	1250mm	
Cabinet Depth	892mm	
Cabinet Weight	400kg	
Airflow	5000m3/h	
Sound Level	<60dBa	

Machine supplied with

FUME FILTRATION

Proud Distributor of Purex Products



 \bullet 2 x Main Filter \bullet 3 x Pre-filter \bullet 1 x 4.5m x Fixed Power Cable (No Plug) \bullet 1 x Manual

W: FumeFiltration.com | Jorlink.com T: (336) 288-1613 | E: sales@fumefiltration.com | E: sales@jorlink.com | Jorlink USA.Inc, 3714 Alliance Dr., Suite 100, Greensboro, NC 27407

Large, heavy duty fume extraction unit

Code


Main filter

Description

110624 Ch

Chemical

Connection kits



Technical

7 — 4 — 6 — 3 — 3 — 3

Rear Inlet

LEGEND:

- 1. Air inlet 200mm safe seal
- 2a. Pre-filter pad
- 2b. Pre-filter pleated bag
- 2c. Pre-filter labyrinth bag
- 3. Main filter (carbon location)
- 4. Main filter (HEPA location)
- 5. Clean air returned to the workplace
- 6. Filter locking handles

6

7. Filter indentification labels

Interfacing

Interfacing can remotely start the Purex machine when the connected machine starts.

Interfacing can also warn the connected machine when the Purex machine is in alarm.



10011010





Take a look through our Interfacing Guide to see our extensive range of options

